Tuples

Tuples

A collection of values of various types

```
let person = (“John”, 27, true);
```

```
let person: (&str, i32, bool) = (“John”, 27, true);
```

Tuples

A collection of values of various types

```
let person = (“John”, 27, true);
```

```
let person: (&str, i32, bool) = (“John”, 27, true);
```

- Static - cannot be resized

Tuples

A collection of values of various types

```
let person = (“John”, 27, true);
```

```
let person: (&str, i32, bool) = (“John”, 27, true);
```

- Static - cannot be resized
- Element values can be updated

Tuples

A collection of values of various types

```
let person = (“John”, 27, true);
```

```
let person: (&str, i32, bool) = (“John”, 27, true);
```

- Static - cannot be resized
- Element values can be updated
- Indexed

Tuples

A collection of values of various types

```
let person = (“John”, 27, true);
```

```
let person: (&str, i32, bool) = (“John”, 27, true);
```

- Static - cannot be resized
- Element values can be updated
- Indexed
- Limited to 12 elements

Tuples

Accessing elements

```
println!(“Name: {}”, person.0);
```

Tuples

Accessing elements

```
println!(“Name: {}”, person.0);
```

Updating elements

```
person.0 = “Jack”;
```

Tuples

Accessing elements

```
println!(“Name: {}”, person.0);
```

Updating elements

```
person.0 = “Jack”;
```

Destructuring a tuple

```
let (name, age, employed) = person;
```

Tuples

Accessing elements

```
println!(“Name: {}”, person.0);
```

Updating elements

```
person.0 = “Jack”;
```

Destructuring a tuple

```
let (name, age, employed) = person;
```

number of variables must correspond to number of elements